



TECHNICAL FEATURES

Light tubular frame made of powder-coated chromed steel, equipped with corner bumpers and push handles.

2-sections mattress platform made of wire chromed steel, dim. 1960x660 mm, equipped with sockets for the positioning of IV pole at each corner.

Backrest adjustment by gas spring

Height adjustment by pedal-operated hydraulic pump controlled by a lever fixed at foot-end.
Trendelenburg and reverse Trendelenburg adjustments by gas spring

Base on 4 castors, Ø 200 mm, with simultaneous lock, 1 is directional. Lock is controlled by 2 levers fixed at foot-end of the stretcher. ABS base cover.

Components to be added:

- two collapsible side rails with locking device.
- fireproof and waterproof mattress, resistant to blood, urine, oil and disinfectants, dim. 1840x600x60 h mm

Technical data:

Backrest adjustment: 0° - 75°

Height adjustment: 490 - 900 mm

Trendelenburg adjustments (+/-16°)

Safe working load : 170 kg.

CODE	LO503-221	ITEM REV.	00 of 03/02/2021
DIMENSIONS	2020x780x490/900 h mm		
CND	V0899	RDM	2762680

Classified as Medical Device in class I, complying with Regulation (EU) 2017/745 dated 5 April 2017.
Manufactured in compliance with ISO 9001:2015 & ISO 14001:2015 certificates